

## *MAXUS Q-LS*

**MAXUS Q-LS** is a water extendible, general purpose semi-synthetic cutting and grinding fluid formulated to perform exceptionally in a variety of machine operations.

**MAXUS Q-LS**, when mixed with water, forms a water-thin transparent micro-emulsion that exhibits excellent cooling properties for superior finishes and increased tool life. **Q-LS** is recommended for use when machining, sawing and grinding ferrous and non ferrous materials where machinability requirements range from mild to moderately severe. The substantial amount of EP additives and high mole weight polymerized esters yield a non-tacky, but significantly enhanced performance in boundary lubrication. For this reason, the **Q-LS** is also recommended for use in stamping, tube rolling, drawing and forming operations where the severity of the application is light to moderate. The opaque emulsion is non-foaming, silicon and chlorine free, and is easy to mix in both soft and hard water.

**MAXUS Q-LS** remains highly transparent to afford the machine operator full view of the work.

The effective biostatic system formulated into the **Q-LS** yields a high resistance to microbial degradation and rancidity; this allows for longer coolant life in machine sumps and central coolant systems without special maintenance procedures. Unlike many solubles and synthetics, the **Q-LS** remains fluid in and on the surfaces of the machining center allowing slideways, chucks, and tooling to work freely without a hard-to-clean dry or sticky residue.

**MAXUS Q-LS** incorporates a corrosion-inhibitor package provides excellent protection for machine tool surfaces and parts in process. **Q-LS** is formulated free of Boron, DCHA, and DEA. **MAXUS Q-LS** also contains an inhibitor to prevent galvanic corrosion between stacked parts. This feature makes the **Q-LS** well suited for the machining of cast iron, most alloys of copper, and a variety of machine operations on aluminum alloys.

### Recommended Starting Dilutions

Machining - drilling, turning, milling, tapping, boring, and reaming  
1 : 20 ( 5% ) to 1 : 10 ( 10% )

Sawing / Grinding - centerless, surface, cylindrical, internal.  
1 : 20 ( 5% ) to 1 : 14 ( 7% )

### Concentration Check

Concentration	1:33 (3%)	1:25 (4%)	1:20 (5%)	1:17 (6%)	1:14 (7%)	1:12 (8%)	1:11 (9%)	1:10 (10%)
Refractometer Reading ---- (Brix Scale)	----	2.2	2.6	3.0	3.4	3.8	4.2	

## MAXUS Q-LS Performance Advantages

- + Unique Tool / Wheel Performance - Excellent cooling properties and extreme pressure lubricity combine to provide extended tool life.
- + Excellent Cleanliness - Remains semi-transparent ; good settling properties provide for ease of contaminant removal; low foaming; non-drying on machine surfaces.
- + Exceptional Corrosion Control - Prevents in-process corrosion of work pieces and machine tool parts.
- + Long Life - More tolerant of hard water and tramp oils and has a high resistance to rancidity for longer sump life.
- + High operator acceptance.

## Typical Physical Characteristics

Specific Gravity, 60/60F	.	.	.	.	.	1.08
Flash Point, COC F	.	.	.	.	.	none
pH, fresh, 1:20 (5%) dilution	.	.	.	.	.	9.6-9.8
Color, dilution	.	.	.	.	.	opaque/undyed or blue-green
Color, concentrate	.	.	.	.	.	undyed or blue- Also available in Red upon request

## Packaging

MAXUS Q-LS is available in 55 gallon steel drums, totes and bulk quantities.

For additional information, product samples, etc., please contact;  
MAXIM OIL & CHEMICAL COMPANY  
Fort Worth, Texas, 76140 - Metro (817) 654-4456  
[www.maximoil@hotmail.com](mailto:www.maximoil@hotmail.com)

**DISCLAIMER** Information contained herein is believed to be correct and reliable. However, Maxim Petrochemical Corporation does not assume liability for it or for recommendations of our representatives inasmuch as conditions and methods of use are beyond our control. Further, we make no warranty, expressed or implied, of any kind regarding those products or their use and purchaser assumes all risks of use or handling either in accordance with directions or not.

**MANUFACTURER DISCLAIMER** The information and recommendations contained herein are, to the best of the knowledge and belief of Maxim Petrochemical Corporation, accurate and reliable as of the date issued. Maxim does not warrant or guarantee their reliability, and Maxim shall not be liable for any loss or damage arising out of use thereof. The information and recommendations are for the user's consideration and examination. Conditions of use are beyond Maxim's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risk of their use, handling, and disposal of the product(s). This information relates only to the product(s) designated herein and does not relate to its use in combination with any other material or in any other process.